



BARGE: GM 1018

ULLAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 PORT	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-5/8	- 01-5/8	02-1/8	- 02-1/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8
3 STBD	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-5/8	- 01-5/8	02-1/8	- 02-1/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS - 01-0/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11"

LENGTH BETWEEN DRAFT MARKS: 262'-00"

August 18, 2016



BARGE: GM 1018
JEFFBOAT 15-2113

2 STBD
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-01 1/2"

Table with 24 columns (IN 0 to IN 16 FT.) and 24 rows (0 to 3/4). Each cell contains a numerical value representing capacity in barrels.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 08/12/2016 BY: JM
DATE COMPUTED: 08/18/2016 BY: CL
DATE ISSUED: 08/18/2016

Signature of the responsible party

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-10 1/2"

Table with 24 columns (IN 0 to IN 16 FT.) and 24 rows (0 to 3/4). Each cell contains capacity values in barrels of 42 U.S. gallons.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 08/12/2016 BY: JM
DATE COMPUTED: 08/18/2016 BY: CL
DATE ISSUED: 08/18/2016



BARGE: GM 1018 JEFFBOAT 15-2113

FUEL TANK ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT: 4'-02 1/8"

IN	0 FT.	IN	0 FT.	IN	1 FT.	IN	1 FT.	IN	2 FT.	IN	2 FT.	IN	3 FT.	IN	3 FT.	IN	4 FT.	IN	4 FT.
0		6	15,298	0	13,453	6	11,335	0	9,218	6	7,101	0	4,984	6	2,867	0	750	6	
1/8		1/8	15,290	1/8	13,408	1/8	11,291	1/8	9,174	1/8	7,057	1/8	4,940	1/8	2,823	1/8	706	1/8	
1/4		1/4	15,268	1/4	13,364	1/4	11,247	1/4	9,130	1/4	7,013	1/4	4,896	1/4	2,779	1/4	662	1/4	
3/8		3/8	15,246	3/8	13,320	3/8	11,203	3/8	9,086	3/8	6,969	3/8	4,852	3/8	2,735	3/8	617	3/8	
1/2		1/2	15,224	1/2	13,276	1/2	11,159	1/2	9,042	1/2	6,925	1/2	4,808	1/2	2,691	1/2	573	1/2	
5/8		5/8	15,202	5/8	13,232	5/8	11,115	5/8	8,998	5/8	6,881	5/8	4,764	5/8	2,646	5/8	529	5/8	
3/4		3/4	15,180	3/4	13,188	3/4	11,071	3/4	8,954	3/4	6,837	3/4	4,719	3/4	2,602	3/4	485	3/4	
7/8		7/8	15,158	7/8	13,144	7/8	11,027	7/8	8,910	7/8	6,792	7/8	4,675	7/8	2,558	7/8	441	7/8	
1		7	15,136	1	13,100	7	10,983	1	8,865	7	6,748	1	4,631	7	2,514	1	397	7	
1/8		1/8	15,114	1/8	13,056	1/8	10,938	1/8	8,821	1/8	6,704	1/8	4,587	1/8	2,470	1/8	353	1/8	
1/4		1/4	15,077	1/4	13,011	1/4	10,894	1/4	8,777	1/4	6,660	1/4	4,543	1/4	2,426	1/4	309	1/4	
3/8		3/8	15,040	3/8	12,967	3/8	10,850	3/8	8,733	3/8	6,616	3/8	4,499	3/8	2,382	3/8	265	3/8	
1/2		1/2	15,004	1/2	12,923	1/2	10,806	1/2	8,689	1/2	6,572	1/2	4,455	1/2	2,338	1/2	221	1/2	
5/8		5/8	14,967	5/8	12,879	5/8	10,762	5/8	8,645	5/8	6,528	5/8	4,411	5/8	2,294	5/8	176	5/8	
3/4		3/4	14,930	3/4	12,835	3/4	10,718	3/4	8,601	3/4	6,484	3/4	4,367	3/4	2,249	3/4	132	3/4	
7/8		7/8	14,893	7/8	12,791	7/8	10,674	7/8	8,557	7/8	6,440	7/8	4,322	7/8	2,205	7/8	88	7/8	
2		8	14,857	2	12,747	8	10,630	2	8,513	8	6,395	2	4,278	8	2,161	2	44	8	
1/8		1/8	14,820	1/8	12,703	1/8	10,586	1/8	8,468	1/8	6,351	1/8	4,234	1/8	2,117	1/8	0	1/8	
1/4		1/4	14,776	1/4	12,659	1/4	10,542	1/4	8,424	1/4	6,307	1/4	4,190	1/4	2,073	1/4		1/4	
3/8		3/8	14,732	3/8	12,615	3/8	10,497	3/8	8,380	3/8	6,263	3/8	4,146	3/8	2,029	3/8		3/8	
1/2		1/2	14,688	1/2	12,570	1/2	10,453	1/2	8,336	1/2	6,219	1/2	4,102	1/2	1,985	1/2		1/2	
5/8		5/8	14,643	5/8	12,526	5/8	10,409	5/8	8,292	5/8	6,175	5/8	4,058	5/8	1,941	5/8		5/8	
3/4		3/4	14,599	3/4	12,482	3/4	10,365	3/4	8,248	3/4	6,131	3/4	4,014	3/4	1,897	3/4		3/4	
7/8		7/8	14,555	7/8	12,438	7/8	10,321	7/8	8,204	7/8	6,087	7/8	3,970	7/8	1,852	7/8		7/8	
3		9	14,511	3	12,394	9	10,277	3	8,160	9	6,043	3	3,925	9	1,808	3		9	
1/8		1/8	14,467	1/8	12,350	1/8	10,233	1/8	8,116	1/8	5,999	1/8	3,881	1/8	1,764	1/8		1/8	
1/4		1/4	14,423	1/4	12,306	1/4	10,189	1/4	8,072	1/4	5,954	1/4	3,837	1/4	1,720	1/4		1/4	
3/8		3/8	14,379	3/8	12,262	3/8	10,145	3/8	8,027	3/8	5,910	3/8	3,793	3/8	1,676	3/8		3/8	
1/2		1/2	14,335	1/2	12,218	1/2	10,100	1/2	7,983	1/2	5,866	1/2	3,749	1/2	1,632	1/2		1/2	
5/8		5/8	14,291	5/8	12,173	5/8	10,056	5/8	7,939	5/8	5,822	5/8	3,705	5/8	1,588	5/8		5/8	
3/4		3/4	14,246	3/4	12,129	3/4	10,012	3/4	7,895	3/4	5,778	3/4	3,661	3/4	1,544	3/4		3/4	
7/8		7/8	14,202	7/8	12,085	7/8	9,968	7/8	7,851	7/8	5,734	7/8	3,617	7/8	1,500	7/8		7/8	
4		10	14,158	4	12,041	10	9,924	4	7,807	10	5,690	4	3,573	10	1,456	4		10	
1/8		1/8	14,114	1/8	11,997	1/8	9,880	1/8	7,763	1/8	5,646	1/8	3,529	1/8	1,411	1/8		1/8	
1/4		1/4	14,070	1/4	11,953	1/4	9,836	1/4	7,719	1/4	5,602	1/4	3,484	1/4	1,367	1/4		1/4	
3/8		3/8	14,026	3/8	11,909	3/8	9,792	3/8	7,675	3/8	5,557	3/8	3,440	3/8	1,323	3/8		3/8	
1/2		1/2	13,982	1/2	11,865	1/2	9,748	1/2	7,630	1/2	5,513	1/2	3,396	1/2	1,279	1/2		1/2	
5/8		5/8	13,938	5/8	11,821	5/8	9,703	5/8	7,586	5/8	5,469	5/8	3,352	5/8	1,235	5/8		5/8	
3/4		3/4	13,894	3/4	11,776	3/4	9,659	3/4	7,542	3/4	5,425	3/4	3,308	3/4	1,191	3/4		3/4	
7/8		7/8	13,850	7/8	11,732	7/8	9,615	7/8	7,498	7/8	5,381	7/8	3,264	7/8	1,147	7/8		7/8	
5		11	13,805	5	11,688	11	9,571	5	7,454	11	5,337	5	3,220	11	1,103	5		11	
1/8	15,349	1/8	13,761	1/8	11,644	1/8	9,527	1/8	7,410	1/8	5,293	1/8	3,176	1/8	1,059	1/8		1/8	
1/4	15,342	1/4	13,717	1/4	11,600	1/4	9,483	1/4	7,366	1/4	5,249	1/4	3,132	1/4	1,014	1/4		1/4	
3/8	15,334	3/8	13,673	3/8	11,556	3/8	9,439	3/8	7,322	3/8	5,205	3/8	3,087	3/8	970	3/8		3/8	
1/2	15,327	1/2	13,629	1/2	11,512	1/2	9,395	1/2	7,278	1/2	5,160	1/2	3,043	1/2	926	1/2		1/2	
5/8	15,320	5/8	13,585	5/8	11,468	5/8	9,351	5/8	7,233	5/8	5,116	5/8	2,999	5/8	882	5/8		5/8	
3/4	15,312	3/4	13,541	3/4	11,424	3/4	9,307	3/4	7,189	3/4	5,072	3/4	2,955	3/4	838	3/4		3/4	
7/8	15,305	7/8	13,497	7/8	11,380	7/8	9,262	7/8	7,145	7/8	5,028	7/8	2,911	7/8	794	7/8		7/8	

NOTE: GAUGE POINT: 8" DIAMETER HATCH.

DATE STRAPPED: 08/12/2016 BY: JM
DATE COMPUTED: 08/18/2016 BY: CL
DATE ISSUED: 08/18/2016

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.