



BARGE: GM 7001

INNAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
1 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 PORT	- 00-5/8	00-5/8	- 01-1/8	01-1/8	- 01-3/4	01-3/4	- 02-3/8	02-3/8	- 02-7/8	02-7/8	- 03-1/2	03-1/2
3 STBD	- 00-5/8	00-5/8	- 01-1/8	01-1/8	- 01-3/4	01-3/4	- 02-3/8	02-3/8	- 02-7/8	02-7/8	- 03-1/2	03-1/2

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS 01-1/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED INNAGE IS 4'-01 1/8"

LENGTH BETWEEN DRAFT MARKS: 262'-00"

November 7, 2017

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-01 3/8"

Table with 25 columns (0 to 15 FT.) and 25 rows (0 to 15 FT.). Each cell contains a numerical value representing capacity in barrels. The table is a grid where the first column and row are labeled '0', and subsequent columns and rows are labeled with their respective foot measurements (e.g., 1/4, 1/2, 3/4, 1, 1 1/4, etc.).

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 09/15/2017 BY: JM
DATE COMPUTED: 11/07/2017 BY: CL
DATE ISSUED: 11/07/2017

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK REFERENCE GAUGE HEIGHT: 16'-01 1/2"

Table with columns for height (0 to 15 FT) and corresponding capacity values in barrels. Each height row includes four fractional increments (1/4, 1/2, 3/4).

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 09/15/2017 BY: JM
DATE COMPUTED: 11/07/2017 BY: CL
DATE ISSUED: 11/07/2017



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-01 3/4"

Table with columns for depth (0 to 15 FT.) and rows for height (0 to 11 FT.). Each cell contains capacity values in barrels for different gauge heights and depths.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 09/15/2017 BY: JM
DATE COMPUTED: 11/07/2017 BY: CL
DATE ISSUED: 11/07/2017

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-10 1/2"

Table with columns for depth (0 to 15 FT) and corresponding capacity values in barrels, including sub-columns for 1/4, 1/2, and 3/4 increments.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 09/15/2017 BY: JM
DATE COMPUTED: 11/07/2017 BY: CL
DATE ISSUED: 11/07/2017

Signature of the official certifying the chart.



BARGE: GM 7001

JEFFBOAT 16-2297

FUEL TANK INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT: 6'-11 1/8"

0 FT.		0 FT.		1 FT.		1 FT.		2 FT.		2 FT.		3 FT.		3 FT.		4 FT.		4 FT.		5 FT.		5 FT.		6 FT.		6 FT.		
0	0	6	1,188	0	2,376	6	3,564	0	4,751	6	5,939	0	7,127	6	8,315	0	9,503	6	10,691	0	11,878	6	13,066	0	14,254	6		

NOTE: GAUGE POINT: 8" DIAMETER HATCH.

DATE STRAPPED: 09/15/2017 BY: JM
 DATE COMPUTED: 11/07/2017 BY: CL
 DATE ISSUED: 11/07/2017

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.